

ENGINE

- John Deere® RG6135HFG495 - turbocharged, diesel engine
 - Standby - 634 hp @ 1800 rpm
 - Prime – 571 hp @ 1800 rpm
 - 6 cylinder
 - 13.5 L displacement
 - Interim Tier IV approved
- Steel, single wall fuel tank
 - 616 gal. (1738 L) capacity
 - 20 hr. run time – full load
 - Fuel tank built into skid of generator set
- Fuel consumption at prime:
 - 100% - 28.4 gph (107.6 Lph)
 - 75% - 20.8 gph (78.7 Lph)
 - 50% - 14.2 gph (53.7 Lph)
- 120% liquid containment
- Cooling system capable of operating at 120°F (49°C) ambient
- Low coolant shutdown
- Radiator and oil drains plumbed to exterior
- Rubber vibration dampers isolate engine/generator from frame
- Disposable air filter - paper element
- In-line engine block heater
- Utilizes DOC / DPF exhaust filter
- Variable Geometry Turbocharger (VGT)
- 60 Hz engine/generator
- Electronic isochronous governing

GENERATOR

- Marathon Electric®
 - Brushless
 - PMG Generator - critical grade power quality
 - 4 pole
 - Class H insulation
- Voltage regulation +/- 0.5% with Magnum PM600 Voltage Regulator

SYSTEM OUTPUTS

- Link / Reconnect Board:
 - Three phase – 120 / 208V Low Wye
 - Three phase – 277 / 480V High Wye
 - 419 kW / 524 kVA – standby, three phase
 - 379 kW / 474 kVA – prime, three phase

SYSTEM CONTROLS

- Power Zone® controller and display
 - Backlit, 800 x 480 pixel resolution color display
 - -40°F to 185°F (-40°C to 85°C) operating temperature range
 - Automatic coarse voltage adjustment
 - Integrated fine voltage adjustment
 - PLC functionality
- Push buttons for easy operation
 - Manual or Auto Start
 - Engine Start
 - Engine Stop/Reset
 - Alarm Mute
 - Operator Screens
 - Home
 - Engine
 - Generator
 - Voltage Adjust
 - Scrolling Arrows for Diagnostic Information
 - Engine diagnostic display
 - Oil pressure
 - Engine temperature
 - Fuel level
 - Battery
 - After treatment inlet/outlet temperature
 - Ash/soot levels
 - Generator diagnostic display
 - System kW output display
 - Line output & frequency display
 - Alarms
 - Warning
 - Shutdown
 - Electrical Trip
 - Engine
 - Alarm list – warnings / shutdowns; 250 event history log – date/time stamp
 - Fuel level: warning – 15%; shutdown – 5%
 - Over speed protection: shutdown – 115%
 - Oil pressure: warning – 25 psi; shutdown – 20 psi
 - Coolant temperature: warning – 220°F (104°C); shutdown – 230°F (110°C)
 - Battery voltage: over – 15VDC; under – 11VDC
 - Generator over voltage: warning – 110%; electrical trip – 111%
 - Generator under voltage: warning – 87%; electrical trip – 86%
 - Generator over frequency: warning – 105%; electrical trip – 110%
 - Generator under frequency: warning – 95%; electrical trip – 90%

SYSTEM CONTROLS (continued)

- Inputs/Outputs
- Auto Schedule
- Status
- Configuration of controller, firmware and connections

ELECTRICAL CONTROLS

- Remote start / stop contacts located in lug box
- Lockable control box door with diagnostics window
- Lockable lug box with safety switch
 - Trips main breaker when door is opened
 - Disables voltage regulator
- Cable entry guides to the lug box
 - Restricts access of foreign objects
- Output ground connection lug inside lug box
- 1600A main breaker with shunt trip
- Convenience receptacles with individual breakers (restricted use in high wye mode)
 - (2) 120V 20 Amp GFCI duplex outlets – (NEMA 5-20R type)
 - (3) 125 / 250V 50 Amp, 3 pole, 4 wire Twistlock (Non-NEMA 6369)
 - Buck Transformer kit – Provides 120V at GFCI outlets when in 277/480V
- (2) 1000CCA wet cell batteries
 - Battery disconnect switch
 - 10A trickle battery charger

ENCLOSURE

- Aluminum, sound attenuated enclosure
 - UV & fade resistant, high temperature cured, white polyester powder paint
 - Insulated and baffled
 - 68 dB(A) @ 23 ft. (7 m) – prime power
- Fully lockable enclosure including doors and fuel fill
- Emergency stop switch located on outside of enclosure
- Central lifting point
- Multi-lingual operating/safety decals
- Document holder with operating manual including AC/DC wiring diagrams

TRAILER

- DOT approved tail, side, brake, and directional lights; recessed rear lights
- Transportation tie downs
- Safety chains with spring loaded safety hooks
- 3 in. (76.2 mm) lunette ring hitch
- (3) 8000 lb. (3629 kg) axles with surge brakes
- 15000 lb. (6804 kg) tongue jack with footplate
- ST215/75R17.5 tubeless tires – 16 ply

WEIGHT & DIMENSIONS

- Skid mounted
 - Dry weight: 12690 lbs. (5756 kg)
 - Operating weight: 17125 lbs. (7768 kg)
 - 175 x 60 x 96 in. (4.34 x 1.52 x 2.44 m)
- Trailer mounted
 - Dry weight: 15940 lbs. (7230 kg)
 - Operating weight: 20375lbs. (9241 kg)
 - 250 x 102 x 116 in. (6.35 x 2.59 x 2.95 m)

WARRANTY

2 Years / 2000 Hours

CERTIFICATIONS

CSA Certified